

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/053960 A1

(51) International Patent Classification⁷: **B41J 2/175**

(21) International Application Number:
PCT/GB2004/005104

(22) International Filing Date: 3 December 2004 (03.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0328013.8 3 December 2003 (03.12.2003) GB
0329001.2 15 December 2003 (15.12.2003) GB
0404432.7 27 February 2004 (27.02.2004) GB

(71) Applicant (for all designated States except US): **DYNAMIC CASSETTE INTERNATIONAL LTD.** [GB/GB]; Marsh Lane, Boston, Lincolnshire PE21 7TX (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **STUDHOLME, John, William** [GB/GB]; Marsh Lane, Boston, Lincolnshire PE21 7TX (GB). **VICKERS, Kevin** [GB/GB]; Marsh Lane, Boston, Lincolnshire PE21 7TX (GB).


(74) Agents: **DEMPSTER, Benjamin, John, Naftel et al.**; Withers & Rogers, Goldings House, 2 Hays Lane, London SE1 2HW (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: AN INK CARTRIDGE



(57) Abstract: An ink cartridge (10) comprises an ink tank (12), the ink tank (12) comprising a first chamber (34), the cartridge (10) including an air vent (16) and an ink supply outlet (14) both opening into the first chamber (34) the cartridge (10) further including means (33) defining a volume in which air and ink can collect to form a buffer against expansion or contraction of ink and air in the first chamber (34) to prevent leakage from the cartridge (10).

WO 2005/053960 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*